



## Infrared Weatherproof IP Camera GSC3615

The GSC3615 is a weather-proof Infrared (IR) wall-mounted bullet IP camera with a 3.6mm lens - making it ideal for wide-angle monitoring of nearby subjects in environments such as banks, hotels, retail, offices, warehouses, and building entrances. This device supports motion detection and smart infrared technology for white balance and exposure to monitor activity at night in outdoor or dark enclosed spaces. The GSC3615 can be managed with GSURF Pro, Grandstream's free video management software, along with other ONVIF-compliant video management systems. It pairs with Grandstream's video phones and GSC3570 HD intercom and facility control station for active end-point monitoring and facility control. By adding weatherproof capabilities, this is an ideal device for increasing security and facility management in any indoor or outdoor area.



Supports motion detection



Smart infrared technology for optimal white balance and exposure



Built-in PoE to power the device and provide a network connection



Supports alert notifications via outbound voice or video call & email screenshot



IP66-level weatherproof capability



Primary stream and Secondary stream



SIP/VoIP support for video and audio streaming to endpoints (external microphone required)

<b>Network Protocol</b>	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, LLDP-MED, TLS, SRTP
<b>Image Sensor Resolution</b>	1/2.9" CMOS Sensor, 2 megapixel (2MP), 1920(H)*1080(V) resolution
<b>Video Compression</b>	H.264/H.265/JPEG/MJPEG
<b>Supported Maximum Video Resolution</b>	Primary Stream:1920*1080; 1280*960; 1280*720 Secondary Stream: 1280*720; 704*576; 640*480; 352*288; 320*240
<b>Video Output</b>	Network
<b>Audio</b>	Line-In: 1 x 3.5mm, 1-50mVpp; Line-Out: 1 x 3.5mm, 560Ω, 4.0Vpp
<b>Scanning System</b>	Progressive
<b>Image Configuration</b>	Saturation/Brightness/Contrast/Sharpness, White Balance
<b>Focal Length</b>	Fixed 3.6mm
<b>Infrared LED</b>	2x LED, up to 20M, Auto Control
<b>Ethernet</b>	One RJ-45 (10/100Base-T) Port with PoE
<b>ONVIF</b>	Yes, Profile S
<b>Day/Night</b>	Color/ Black &White (IR-CUT )
<b>Motion Detection</b>	Supported
<b>Language Supported</b>	Multi-Language
<b>Privacy Mask</b>	4 Rectangular Zone
<b>Weatherproof Grade</b>	Metal , IP66-level weatherproof capability
<b>Power</b>	DC12V±10%,1A (Power Adapter NOT Included) PoE: Support IEEE 802.3af
<b>Temperature / Humidity</b>	-20 °C ~ 50 °C, RH95% Max
<b>Weight and Dimensions</b>	171 x 73 x 73mm, 430g
<b>Compliance</b>	FCC, CE, RCM, IC